All seam allowances should be a scant quarter-inch.

Fabric requirements for **ONE** block

- (5) 4½" squares of a SOLID autumn colour
- (4) 4½" squares of an autumn PRINT

Assembly

 Sew together two SOLID squares and one PRINT square into a strip. Press the seams while they are still closed. Then press the seam allowances toward the PRINT.




- 2. Measure the length of your strip. It should be $12\frac{1}{2}$ ". If it measures more than $12\frac{1}{2}$ ", adjust your seam allowance to be bigger; if your strip measures less than $12\frac{1}{2}$ ", adjust your seam allowance to be smaller.
- 3. Repeat steps 1 & 2.
- Sew together one SOLID square and two PRINT squares into a strip. Press the seams while they are still closed. Then press the seam allowances toward the PRINTS.




5. Repeat step 2.



 Place a SOLID-PRINT-SOLID strip, right sides together, with a PRINT-SOLID-PRINT strip. Nest the seams. Sew together. Press the seam while it is still closed. Then open the patch and press the seam allowance to the SOLID-PRINT-SOLID strip.





Assembly for **MULTIPLE** 9P blocks

- A. Cut five 4½" strips of a SOLID autumn colour. Cut four 4½" strips of an autumn PRINT.
- B. Sew together two SOLID-PRINT-SOLID strip sets and one PRINT-SOLID-PRINT strip set. Each strip set should measure 12½" wide. Adjust your seam allowance if necessary. (See step 2 above.)
- C. Sub-cut each strip set into 4½" sections.













D. Repeat steps 6 & 7 above to make 9P blocks.